

# FILT'RAY 2-month shower head filter

Ref. AT030715

Non-sterile



## DESCRIPTION

**FILT'RAY 2-month shower head filter**

**Ref. AT030715**

AQUATOOLS anti-Legionella and all-germ shower filter.  
Device made from MBS.  
Membrane type: tubular microfiltration.  
Membrane made from polyethylene.  
Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.  
Filtration flow rate: 11.9 lpm at 3 bar and 4.5 lpm at 1 bar (filter only, excludes any flow rate restriction in the shower).  
Maximum upstream pressure at the point-of-use: 5 bar.  
Maximum lifespan: 2 months after installation.  
Withstands thermal shocks: 70°C for 30 minutes.  
Withstands chemical shocks: active chlorine levels up to 100 ppm for 2 hours (cumulative total).  
Non-sterile filter.  
CE marked Class I medical device.  
Packaged in boxes of 10.

## TECHNICAL CHARACTERISTICS

**FILT'RAY 2-month shower head filter - Ref. AT030715**

|            |                                                                                                          |
|------------|----------------------------------------------------------------------------------------------------------|
| Connector  | M1/2"                                                                                                    |
| Technology | Point-of-use filtration                                                                                  |
| Height     | 70mm                                                                                                     |
| Length     | 225mm                                                                                                    |
| Flow rate  | 11.9 lpm at 3 bar, 4.5 lpm at 1 bar                                                                      |
| Lifespan   | 2 months                                                                                                 |
| Norms      | <b>ACS</b> <b>CE</b>  |

## ADVANTAGES



Anti-Legionella and all-germ



Lifespan: 2 months from installation



Bubl'air Wash: longer filter life



Rapid installation with no tools required

