

# **FILT'RAY 3-month shower** head filter

Ref. AT030724

Non-sterile



## **DESCRIPTION**

#### FILT'RAY 3-month shower head filter

Ref. AT030724

AQUATOOLS anti-Legionella and all-germ shower filter.

Device made from MBS.

Membrane type: tubular microfiltration.

Membrane made from polyethylene.

Pore cut-off threshold: 0.1μm nominal and 0.2μm absolute sterilising grade.

Filtration flow rate: 11.9 lpm at 3 bar and 4.5 lpm at 1 bar (filter only, excludes any flow rate restriction in the shower). Maximum upstream pressure at the point-of-use: 5 bar.

Maximum lifespan: 3 months from installation. Withstands thermal shocks: 70°C for 30 minutes.

Withstands chemical shocks: active chlorine levels up to 100 ppm for 3 hours

(cumulative total). Non-sterile filter.

CE marked Class I medical device.

Packaged in boxes of 10.

## **ADVANTAGES**



Anti-Legionella and all-germ



Lifespan: 3 months from installation



Bubl'air Wash: longer filter life



Rapid installation with no tools required

### **TECHNICAL CHARACTERISTICS**

#### FILT'RAY 3-month shower head filter - Ref. AT030724

Connector	M1/2"
Technology	Point-of-use filtration
Height	70mm
Length	225mm
Flow rate	11.9 lpm at 3 bar, 4.5 lpm at 1 bar
Lifespan	3 months
Norms	ACS ( € WRAS

