FILT'RAY 2G 1-month tap filter

Ref. AT030718

Sterile

DESCRIPTION

FILT'RAY 2G 1-month tap filter
Ref. AT030718

AQUATOOLS anti-Legionella and all-germ tap filter, shower spray.
Device made from MBS.
Membrane type: tubular microfiltration.
Membrane made from polyethylene.
Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.
Filtration flow rate: 6.3 lpm at 3 bar and 2.2 lpm at 1 bar
(filter only, excludes any flow rate restriction in the tap).
Maximum upstream pressure at the point-of-use: 5 bar.
Maximum lifespan: 1 month from installation.
Withstands thermal shocks: 70°C for 30 minutes.
Withstands chemical shocks: active chlorine levels up to 100 ppm
for 1 hour (cumulative total).
Sterile filter.
FILT'RAY 2G sterile disposable water filters are:
CE marked Class I Medical Devices in Europe that comply with directive 93/42/CEE;
Class II Medical Devices in the U.S.A. with FDA-510(K) clearance;
Class I Medical Devices in Canada that comply with SOR/98-282.
Packaged in boxes of 10, each filter is individually wrapped and sterile.

ADVANTAGES

- Anti-Legionella and all-germ
- Lifespan: 1 month from installation
- Bubl'air Wash: longer filter life
- Rapid installation with no tools required

TECHNICAL CHARACTERISTICS

FILT'RAY 2G 1-month tap filter - Ref. AT030718

Technology	Point-of-use filtration
Height	72mm
Length	75mm
Flow rate	6.3 lpm at 3 bar, 2.2 lpm at 1 bar
Lifespan	1 month
Norms	ACS CE WRAS



© AQUATOOLS