

# FILT'RAY 3-month tap filter

Ref. AT030729

Non-sterile



## DESCRIPTION




**FILT'RAY 3-month tap filter**

**Ref. AT030729**

AQUATOOLS anti-Legionella and all-germ tap filter.  
Device made from MBS.  
Membrane type: tubular microfiltration.  
Membrane made from polyethylene.  
Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.  
Filtration flow rate: 6.3 lpm at 3 bar and 2.2 lpm at 1 bar (filter only, excludes any flow rate restriction in the tap).  
Maximum upstream pressure at the point-of-use: 5 bar.  
Maximum lifespan: 3 months from installation.  
Withstands thermal shocks: 70°C for 30 minutes.  
Withstands chemical shocks: active chlorine levels up to 100 ppm for 3 hours (cumulative total).  
Non-sterile filter.  
CE marked Class I medical device.  
Packaged in boxes of 10.

## TECHNICAL CHARACTERISTICS

**FILT'RAY 3-month tap filter - Ref. AT030729**

Technology	Point-of-use filtration
Height	72mm
Length	75mm
Flow rate	6.3 lpm at 3 bar, 2.2 lpm at 1 bar
Lifespan	3 months
Norms	  

## ADVANTAGES



Anti-Legionella and all-germ



Lifespan: 3 months from installation



Bubl'air Wash: longer filter life



Rapid installation with no tools required

