

# FILT'RAY wall-mounted fixed shower, 4 months

Ref. AT030742

Non-sterile



## DESCRIPTION




**FILT'RAY wall-mounted fixed shower, 4 months**

**Ref. AT030742**

AQUATOOLS anti-Legionella and all-germ filter for fixed, wall-mounted showers (shower panels).  
 Device made from MBS.  
 Membrane type: tubular microfiltration.  
 Membrane made from polyethylene.  
 Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.  
 Filtration flow rate: 13.1 lpm at 3 bar and 3.9 lpm at 1 bar (filter only, excludes any flow rate restriction in the shower).  
 Maximum upstream pressure at the point-of-use: 5 bar.  
 Maximum lifespan: 4 months from installation.  
 Withstands thermal shocks: 70°C for 30 minutes.  
 Withstands chemical shocks: active chlorine levels up to 100 ppm for 4 hours (cumulative total).  
 Non-sterile filter.  
 CE marked Class I medical device.  
 Packaged in boxes of 10.

## TECHNICAL CHARACTERISTICS

**FILT'RAY wall-mounted fixed shower, 4 months - Ref. AT030742**

Technology	Point-of-use filtration
Height	72mm
Length	75mm
Flow rate	13.1 lpm at 3 bar and 3.9 lpm at 1 bar
Lifespan	4 months
Norms	  

## ADVANTAGES



Anti-Legionella and all-germ



Lifespan: 4 months from installation



Bubl'air Wash: longer filter life



Rapid installation with no tools required

