

# FILT'RAY 2-month shower head filter

Ref. AT20261

Sterile



## DESCRIPTION




**FILT'RAY 2-month shower head filter**

**Ref. AT20261**

AQUATOOLS anti-Legionella and all-germ tap filter, laminar.  
 Device made from ABS.  
 Membrane type: tubular microfiltration.  
 Membrane made from polyethylene.  
 Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.  
 Qualified water volume per duration of use: 6,000 litres.  
 Filtration flow rate: 6 lpm at 1 bar, 11.2 lpm at 3 bar and 13 lpm at 5 bar (filter only, excludes any flow rate restriction in the tap).  
 Maximum upstream pressure at the point-of-use: 5 bar.  
 Maximum lifespan: 2 months after installation.  
 Resistance to thermal shocks: 70°C for 30 minutes.  
 Resistance to chemical shocks: active chlorine levels up to 100 ppm for 2 hours (cumulative total).  
 Sterile filter.  
 Medical device CE Class Is.  
 Weight: empty filter 105g / full filter 186g.  
 Reference for a single unit. Must be ordered in multiples of 10.  
 Packaged in boxes of 10 units.

## TECHNICAL CHARACTERISTICS

**FILT'RAY 2-month shower head filter - Ref. AT20261**

Connector	M1/2"
Height	62mm
Length	194mm
Flow rate	6 lpm at 1 bar, 11.2 lpm at 3 bar and 13 lpm at 5 bar
Diameter	56mm
Lifespan	2 months
Norms	ACS   

## ADVANTAGES



Anti-legionella and all-germ



Space saving



Lifespan: 2 months after installation



Quick to install without tools

