

FILT'RAY 4 month shower filter

Ref. AT030716

Sterile



DESCRIPTION

FILT'RAY 4 month shower filter

Ref. AT030716

AQUATOOLS anti-Legionella and all-germ shower filter.
Device made from MBS.
Membrane type: tubular microfiltration.
Membrane made from polyethylene.
Pore cut-off threshold: 0.1µm nominal and 0.2µm absolute sterilising grade.
Filtration flow rate: 11.9 lpm at 3 bar and 4.5 lpm at 1 bar (filter only, excludes any flow rate restriction in the shower valve).
Maximum upstream pressure at the point-of-use: 5 bar.
Maximum lifespan: 4 months from installation.
Withstands thermal shocks: 70°C for 30 minutes.
Withstands chemical shocks: active chlorine levels up to 100 ppm for 4 hours (cumulative total).
Sterile filter.
FILT'RAY sterile disposable water filters are:
CE marked Class I Medical Devices in Europe that comply with directive 93/42/CEE;
Class II Medical Devices in the U.S.A. with FDA-510(K) clearance;
Class I Medical Devices in Canada that comply with SOR/98-282.
Packaged in boxes of 10, each filter is individually wrapped and sterile.

ADVANTAGES



Anti-Legionella and all-germ



Lifespan: 4 months from installation



Rapid installation with no tools required

TECHNICAL CHARACTERISTICS

FILT'RAY 4 month shower filter - Ref. AT030716

Supply	M1/2"
Technology	Point-of-use filtration
Height	70mm
Length	225mm
Flow rate	11.9 lpm at 3 bar and 4.5 lpm at 1 bar
Lifespan	4 months
Norms	ACS CE

