

# Sediment filter, 5µm

Ref. AT50680

6 months

## DESCRIPTION

Sediment filter, 5µm

Ref. AT50680

PREFILT 5µm sediment filter.  
Retains particles larger than 5µm.  
Filter cartridge can be replaced without changing the filter body.  
Membrane surface area: 0.5m<sup>2</sup>.  
Capacity: 18,000L.  
Maximum lifespan: 6 months.  
Filtration flow rate: 9 lpm (with integrated flow restrictor), 14 lpm (without flow restrictor) at 3 bar.  
Materials: Body and filtration cartridge made of polypropylene. Filter cartridge plastic components made of ABS.  
Temperature: 4 - 38°C.  
Operating pressure: 0.5 - 10 bar.  
Connection type: Tube or G3/8".  
Compatible with and resistant to chemical shocks (active chlorine levels up to 100 ppm for 1 hour (cumulative total) and thermal shocks (70°C for 30 minutes).

## TECHNICAL CHARACTERISTICS

Sediment filter, 5µm - Ref. AT50680

|           |                                                                                       |
|-----------|---------------------------------------------------------------------------------------|
| Supply    | Tube or G3/8"                                                                         |
| Length    | 335mm                                                                                 |
| Flow rate | 9 lpm (with integrated flow restrictor),<br>14 lpm (without flow restrictor) at 3 bar |
| Diameter  | 82mm                                                                                  |
| Lifespan  | 6 months                                                                              |
| Norms     |    |



## ADVANTAGES



Lifespan: 6 months after installation



Sediment filter

